



since 1911
measuring
instruments

LEMAG®

Indicator Type 30-M2

- *robust*
- *precise*
- *reliable*
- *speedrange up to 400 rpm
(600 rpm)*
- *type approved (GL)*
- *incl. ISO 9001 certificate*



All models are fully type approved by Germanischer Lloyd (GL) & incl. ISO 9001 certificate

LEMAG® Indicator Type 30-M2 are well known worldwide. They are for use and application to draw diagrams on medium speed Diesel-Engines (≤ 400 (600) Rpm).

The LEMAG® Indicator Type 30-M2 is available for pressure ranges up to 250 bar. The pressure range are acc. to current latest engine developments.

The standard instrument is equipped with a 30 mm diameter paper drum, on request a 40 mm drum is available.

LEMAG® Indicator Type 30-M2 has a complete scope of supply incl. all accessories complete in a wooden case.

Please note: This indicator is designed to take single readings at a max. of 30 sec. per cylinder.

Spring schedule LEMAG® Indicator Type 30-M2

Piston	Spring-No.	Measuring range
1/5	1	30 bar
1/5	0,6	50 bar
1/5	0,5	60 bar
1/5	0,45	70 bar
1/5	0,4	80 bar
1/5	0,3	100 bar
1/5	0,24	125 bar
1/5	0,2	150 bar
1/5	0,18	175 bar
1/5	0,16	200 bar
1/5	0,12	250 bar

Other ranges on request available
Piston diameter 1/5 = 9,06
Spring no. = scale in mm / 1 Bar

